







Тепловые насосы Solex - Gaggia, серия GAG - SHL.

Model	GAG-	12.0SHL	18.0SHL	24.0SHL	36.0SHL	42.0SHL	52.0HL
Picture							
Remarks		Including wilo brand water pump, water flow switch, expansion tank					
Price	USD
Heating Capacity	kW	12	18	24	36.0	42.0	52.0
Heating power input	kW	2.86	4.29	5.7	4.6×2	5.6×2	7.0×2
Operating current	A	13.00	6.55	8.7	7.0×2	8.5×2	13.0×2
COP	W/W	4.2	4.2	4.2	3.91	3.75	3.75
Cooling Capacity	kW	7.30	13.20	15.50	26.50	31.00	39.00
Heating power input	kW	2.93	4.33	5.08	4.33×2	5.15×2	6.5×2
Operating current	A	11.00	6.60	7.90	6.6×2	7.86×2	9.9×2
EER	W/W	3.05	3.05	3.05	3.05	3.00	3.00
Power supply	V/Ph/Hz	220-240/1/50		380~440/3/50			
Working temperature range	°C	(-)25~43					
Compressor	Type	Scroll(EVI compressor)					
Water side heat exchanger	Type	Plate type					
Air side heat exchanger	Type	High efficiency copper tube(Interior Screw) nested in aluminium fin					
	Fan Type	Low-noise Wide-blade Axial Fan					
Refrigerant	Type	R410a					
	Qty	1.90	2.95	3.15	5.90	6.30	8.00
Operating Control	Type	Full-automatic, intelligence					
	Control panel	LED display, back light					
	Display	Water tank temp., Ambient temp., Time, Operating mode, Discharge temp. Coil temp. Error code					
	Main Function	Setting Time, Time On/Off, Water tank temp., Defrosting cycle, Start temp. of defrosting, Exit temp. of defrosting, Exit cycle of defrosting, Power lost memory					
Defrosting	Type	Automatic 4 Way Valve Reverse					
Protection function		Compressor overload, Discharge temp. and etc.					
Dimensions	Length	mm	865	975	1405	1405	1498
	Width	mm	465	545	800	800	798
	Height	mm	795	1035	1050	1050	1443
Dimensions(Indoor unit)	Width	mm	530	530	800	800	800
	Depth	mm	310	310	310	700	700
	Height	mm	760	760	700	700	700
Unit noise level		dB(A)	52	55	56	58	65
Net / Gross weight		kg	110	125	135	270	290

