

Инверторные тепловые насосы Solex - Gaggia, серия GAG - DC-S.

Model	GAG-	08DC/S	12DC/S	16DC/S	25DC/S	
Picture						
Remarks	Including MITSUBISHI DC inverter compressor, WILO DC inverter water pump, water flow detector, EC inverter fan motor, expansion tank, safety valve, wifi control function, A+++ COP					
Price	USD	
Heating-1(7/6°C,30/35°C)	Rated capacity	kW	8.2	11.7	16.2	25
	Power input	kW	1.84	2.65	3.69	7.75
	COP	W/W	4.45	4.42	4.38	4.35
Heating-2(-15/°C,30/35°C)	Rated capacity	kW	5.38	7.59	10.58	16.4
	Power input	kW	2.14	3.06	4.3	6.69
	COP	W/W	2.51	2.48	2.46	2.45
Heating-3(7/6°C,40/45°C)	Rated capacity	kW	7.8	11.2	15.6	18.8
	Power input	kW	2.2	3.27	3.27	3.43
	COP	W/W	3.54	3.52	3.48	3.45
Cooling-2(35/24°C,12/7°C)	Rated capacity	kW	6.13	8.7	11.8	17.2
	Power input	kW	2.21	3.2	4.4	6.52
	EER	W/W	2.75	2.72	2.68	2.65
Working ambient temperature	°C	(-)25~43				
Power source	V/Ph/Hz	230/1/50	230/1/50	400/3/50	400/3/50	
Compressor type		Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary	
Refrigerant		R410a				
Max current	A	14	17	25	8	
Max power input	kW	3.1	3.55	5.5	8.5	
Max working pressure	Bar	42	42	42	42	
Water proof		IPx4	IPx4	IPx4	IPx4	
Max output water temp.	°C	60	60	60	60	
Max water pressure	Bar	3	3	3	3	
Water pipe size	Inches	1	1	1	1	
Drain water pipe size	mm	15	15	15	15	
Rated water volume	m³/Hour	1.9	1.9	2.7	3.2	
Dimensions	Indoor unit	mm(HxWxL)	730x460x322		730x460x322	730x460x322
	Outdoor unit	mm(HxWxL)	1260x310x830		1331x478x1030	1331x478x1030
Dimensions (Packaged)	Indoor unit	mm(HxWxL)	830x550x425		830x550x425	830x550x425
	Outdoor unit	mm(HxWxL)	1400x520x1070		1480x500x1170	1480x500x1170
Net weight	Indoor unit	Kg	50	52	55	57
	Outdoor unit	Kg	90	100	120	122
Packaged weight	Indoor unit	Kg	58	60	63	65
	Outdoor unit	Kg	100	110	130	132
Noise level	Indoor unit	dB(A)	30		30	30
	Outdoor unit	dB(A)	50	53	55	57

